## **Declaration of performance**

Bitumen granules as additive for the production of asphalts according to European Assesment Document 230012-01-0105



Jansen Recycling B.V.

Postbus 60

5690 AB Son & Breugel

Telefoon: +31 (0)88 877 87 78; website: www.ajansenbv.com Productionlocation: Kanaaldijk Zuid 24, 5691 NL Son & Breugel



0063

20

0063-CPR-107417/01 EAD 230012-01-0105, edition 2017 Systeem 2+

Bitu-RM (ETA 20/1279)

	Dita-NW (ETA 20/12/3)
Declaration	of performences:
European Assesment Document (EAD)	230012-01-0105
	"Additives for asphalt production - additive from bitumen
	granules made from recycled bituminous roofing felt"
BWR 3 Hygiene, health and environment	
Characteristic	Assesment:
Content, emission and release of dangerous substances	Tar: Bitu-RM does not show any signs of tar content in
	accordance with the defined assesment methods.
	PAH (16) contents is < 1.000 mg/kg
	B(a)P content is in average 60 mg/kg
	Bitu-RM does not contain PAH in concentrations that exceed
	the utilization potential limit
BWR 4 Safety and accessibility in use	
Characteristic	Assesment:
Sofeting point Ring & Ball (°C)	≤ 100 °C
Penetration (mm)	≥ 10 (1/10 mm)
Bitumen (binder) content (% <sup>m</sup> / <sub>m</sub> )	≥ 45% ( <sup>m</sup> / <sub>m</sub> )
Foreign matter (% <sup>v</sup> / <sub>v</sub> )	Maximum 2% ( <sup>v</sup> / <sub>v)</sub>
Particle size after bitumen extraction	0-16 mm
The mediana are of the analysis is a sife of the	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

J.M.M. Busser, directeur Son en Breugel,

Versie 101024